Application to Discharge Liquid Trade Wastes into Council's Sewerage System



Manufacturing Industry Category 3

OFFICE USE ONLY						
CATEGORY 3:	Date:	Fee Paid \$	Debtor	HOT KEY:		
For further enquiries	on the applie	cation process, please co	ontact the Liquid Tra	nde Waste Superviso	r on 4350 5515.	
Business Trading Name			Principa	l Business Activity		
Development Application	No. Lot No	D.P.	Parcel N	lo.	House No.	
Street		Suburb			Postcode	
Property Owner's Name			Telepho	Telephone No. / Email		
Address						
Applicant's Name (if different from Property Owner)			Telepho	Telephone No. / Email		
Applicant's Address (if diff	ferent from Pro	operty Owner)	I			
Occupier's Name (if different from Property Owner)			Telepho	Telephone No. / Email		
DESCRIPTION OF FLOW						
Proposed date of Hours of business operation Hours of the day during which discharge take			lischarge takes place			
commencement of discharge to the	Mon-Fri		Mon-Fri	Mon-Fri		
sewerage system	sewerage system Sat			Sat		
	Sun _		Sun			
Average daily discharge to sewer (kL)	charge Maximum rate of discharge to sewer			Maximum daily discharge to sewer (kL)		
Any water supply meter being installed? Yes No	Existing wat	er meter number	Meter lo	ocation		

EXISTING / PROPOSED EQUIPMENT (GREASE ARRESTOR, BASKET ARRESTOR, COOLING PIT, ETC)

Туре	Size/flow rate



Wyong Office: 2 Hely St / PO Box 20 Wyong NSW 2259 | **P** 02 4350 5555 **Gosford Office:** 49 Mann St / PO Box 21 Gosford NSW 2250 | **P** 02 4325 8222 **E** ask@centralcoast.nsw.gov.au | **W** centralcoast.nsw.gov.au | ABN 73 149 644 003

PROPOSED CLEANING SCHEDULE OF PRE-TREATMENT EQUIPMENT AND NAMES OF CONTRACTORS USED				
Pre-treatment equipment	Frequency (weeks)			
Name of Contractor	Contact number			
Location of sampling point				
r grow				
Refer to Council's <u>Liquid Trade Waste Policy</u> for the Liquid Trade Waste Quality Standards, which lists pollutants and their allowable limits				
SUBSTANCES PROHIBITED FROM BEING DISCHARGED TO THE SEWERAGE SYSTEM				
The following substances are prohibited from being discharged to the sewerage system:				
 organochlorine weedicides, fungicides, pesticides, herbicides and substances of a similar nature and/or wastes arising from the preparation of these substances 				
organophosphorus pesticides	and/or waste arising from the preparation of these substances			
any substances liable to produce noxious or poisonous vapours in the sewerage system				
organic solvents and mineral oil				

- any flammable or explosive substances
- discharges from 'Bulk Fuel Depots'
- chromate from cooling towers
- natural or synthetic resins, plastic monomers, synthetic adhesives, rubber and plastic emulsions
- rain, surface, seepage or subsoil water, unless specifically permitted
- solid matter
- any substance assessed as not suitable to be discharged to the sewerage system
- waste liquids that contain pollutants at concentrations which inhibit the sewage treatment process refer National Wastewater Source Management Guideline, July 2008, WSAA
- any other substances listed in a relevant regulation.

Signature of Property Owner/s

Owner's authorisation to making the application is mandatory as per Section 78 of the Local Government Act 1993

Please note that the owner of the property will be billed for water supply, sewerage and liquid trade waste services provided and it is the owner's responsibility to pay such fees and charges within the period specified. The owner may arrange to recover such fees and charges through the lease agreement between the owner and the occupier.

The applicant should be aware that approval of this application does not constitute a guarantee of any future approval of a variation to the approval. This will be dependent on the available capacity of the sewerage system at that time and any future approval must not be assumed. However, alerting the Council to the applicant's future plans and proposals may assist the Council in planning future sewage management and / or infrastructure additions / modifications.

Signature of occupier / applicant

Position in company

Date

Manufacturing Industry Application Attachment Sheet

Please fill out this attachment sheet if your business involves manufacturing processes that discharge liquid trade waste to the sewerage system. In the table below, tick the business type that best describes what your business does.

BUSINESS TYPE				
Abattoir	Cosmetic	Food		
Metal plating / anodising	Paper products	Other (please specify)		

Application to Discharge Liquid Trade Wastes into Council's Sewerage System Additional Details Required For Discharger Category C

The following pages are to be used to include additional information required from businesses that wish to discharge Concurrence Classification C liquid trade wastes to the sewerage system. Please include all details as requested (if insufficient space attach as clearly labelled appendices), and make sure you read the section on substances that must not be discharged to the sewerage system.

Name of processes generating liquid trade waste

Type and quantity of raw materials processed

Description of waste:

- List of all expected pollutants including substances contained in wash down detergents, boiler and cooling water and other sources
- Expected maximum and average concentrations of pollutants
- Sample analysis results of the proposed waste.

Note: The sample analysis tests shall be carried out by a NATA approved laboratory with accreditation for analysis of the nominated pollutants in the application or a laboratory acceptable to NOW.

Acceptable means of sample analysis data collection:

- Sample analysis results from a similar existing process
- Collection of the proposed waste from a trial pre-treatment plant
- Stand alone pre-treatment manufacturer's waste quality expectations
- Configured pre-treatment consultant's calculations based on experience of a similar installation

Attach details and supporting documentation of data collection method.

When detailing the nominated pollutants, where there is no possibility of discharge to the sewerage system because none of the substance is stored or used at the premises, write "NIL".

Pollutant	Acceptance Guideline Limits	
Aluminium (AL)	100 mg/L	
Ammonia (as N)	50 mg/L	
Arsenic (As)	1 mg/L *	
Barium (Ba)	10 mg/L *	
Biological Oxygen Demand (BOD ₅)	600 mg/L	
Biocides	Nil	
Boron (B)	25 mg/L *	
Bromine (Br ₂)	5 mg/L	
Cadmium (Cd)	2 mg/L *	
Chlorinated Hydrocarbons	Nil	
Chlorinated Phenolics	Nil	
Chloride	1000 mg/L	
Chlorine (Cl ₂)	10 mg/L	
Chromate	Nil	
Chromium (cr) (Total) #	5 mg/L *	
Cobalt (Co)	5 mg/L *	
COD	< 3x BOD	
Copper (Cu)	5 mg/L *	
Cyanide	5 mg/L	
Flammable / Explosive substances	Nil	
Fluoride (F)	20 mg/L	
Formaldehyde	50 mg/L	
Grease / Oil	100 mg/L	
Herbicides / Weedicides / Fungicides	Nil	
Iron (Fe)	100 mg/L	
Lead (Pb)	2 mg/L *	
Lithium (Li)	5 mg/L *	
Methylene Blue Active Substances (MBAS)	50 mg/L	
Manganese (Mn)	10 mg/L *	
Mercury (Hg)	0.02	
Molybdenum (Mo)	10 mg/L *	
Nickel (Ni)	5 mg/L *	
Nitrogen (N) (Total Kjeldahl Nitrogen)	100 mg/L	
Pentachlorophenol	Nil	
Pesticides – General	Nil	
Pesticides – Organo-chlorine	Nil	
Pesticides – Organophosphate	Nil	
PCB	Nil	
Petroleum Hydrocarbons (non-flammable)	20 mg/L	
PH	7.0 - 9.0	
Phenolic Compounds	Nil	
Phosphorus (Total)	10 mg/L	
Polynuclear Aromatic Hydrocarbons (PAH)	Nil	

Pollutant	Acceptance Guideline Limits
Selenium (Se)	5 mg/L *
Silver (Ag)	2 mg/L *
Sulphate (SO ₄)	500 mg/L
Sulphide (S)	1 mg/L
Sulphite (SO ₃)	15 mg/L
Suspended Solids (SS or NFR)	300 mg/L
Temperature	38°C maximum
Tin (Sn)	5 mg/L *
Total Dissolved Solids	1000 mg/L
Zinc (Zn)	5 mg/L *
Other Substances	Nil refer notes

Notes to Quality Standards and Excluded Substances

Flow Rate – The maximum daily and instantaneous rate of discharge (kL/h or L/s) is set on the available capacity of the sewer. Large dischargers are required to provide a balancing tank to even out the load on the sewage treatment works.

Colour - No visible colour when the waste is diluted to the equivalent dilution afforded by domestic sewage flow.

Radioactive substances – The discharge must comply with the Radiation Control Act 1900.

Chromium # - Where hexavalent chromium (Cr^{6+}) is present in the process water, pre-treatment will be required to reduce it to the trivalent state (Cr^{3+}), prior to discharge into the sewer.

No discrete oil, fat or grease may be discharged.

Hazardous wastes are totally excluded.

Animal matter (including carcasses but not including human waste), wool, hair, grease, dust, ashes, cinders, soil, rubbish, filth, oil, salt, mud, medical waste, sand, gravel, garbage, offal, vegetable or fruit parings, rags, house refuse, steam or solid matter is prohibited.

Any flammable, volatile solvent or explosive substance are excluded.

Wastes arising from the preparation of pesticides, organo-chlorine weedicides, fungicides, herbicides and substances of a similar nature are not permitted.

Any substance liable to produce noxious or poisonous vapours in the sewerage system is excluded.

Organic solvents and mineral oils are excluded.

Natural or synthetic resins, plastic monomers, synthetic adhesives and rubber plastic emulsions are not permitted.

Waste liquids that contain pollutants at concentrations which inhibit the sewerage treatment process are not permitted – refer to Guidelines for Sewerage Systems: Acceptance of Trade Waste (Industrial Waste) (ARMCANZ/ANZECC, 1994).

The discharge of Hexavalent Chromium (from Chromate compounds) used as corrosion inhibitors or organometallic algicides is not permitted.

Infectious or contagious solid or liquid waste is excluded.

Rain, roof, surface, flood, seepage and / or subsoil waters are not permitted.

Any substance likely to cause injury to personnel employed in the sewerage system or the environment for which the sewage effluent is discharged is not permitted.

Any other matter determined by Council to be of an environmental health or other risk to Council's sewerage system is prohibited.

Substances or mixtures of substances that are not miscible with water are not permitted in the sewer system.

Quality Standards for substances other than those listed in above table in Schedule A are to be determined by Council.

* Total Heavy Metals is the sum of all metals in the waste stream excluding Aluminium, Iron, Manganese and Molybdenum. This shall not exceed 30 mg/L.

The quality of trade waste from some low risk commercial activities in Classification A will exceed guideline limits in this Table. As a higher level of pre-treatment is not cost-effective, such waste is acceptable if the discharger installs and properly operates and maintains the required pre-treatment equipment.

BOD concentration up to 600 mg/L and in some cases higher concentration for low mass loadings may be acceptable if the treatment works has sufficient capacity and odour will not be a problem.

Details of management arrangement of waste streams / wastes that are not permitted or not intended to be discharged to the sewerage
system.

The maximum daily and instantaneous rate of discharge (kL/h or L/s) is set on the available capacity of the sewer. Large dischargers are required to provide a balancing tank to even out the load on the sewage treatment works.

Peak periods of discharge during the day			
Type of discharge			
Batch Flow	Intermittent Flow		Continuous Flow
Detail any special circumstances applicable to the disch	narge, for example:		
 Seasonal discharges Large differences between average and maxi Variations to flow, which avoid peak domesti Retention of discharges for extended periods 	c flows, etc		
Does the proposed installation contain open areas that	t will drain to the couverage system?	YES	
If YES, please give details and attach stormwater draina			

Stormwater is prohibited from being discharged into the Council's sewerage system. The capacity for such flows is not provided in the sewerage system. Therefore, council does not generally accept the discharge of stormwater to the sewerage system.

The discharge of limited quantities of first flush water from sealed liquid trade waste generating areas will be considered where roofing cannot be provided because of safety or other important considerations.					
Reasons why the area cannot be fully or partially roofed and bunded to exclude stormwater					
The dimensions of the area under consideration					
Is the open area sealed? YES NO Estimated volume of the stormwater discharge					
Information on a first flush system, if proposed					
Measures proposed for diverting stormwater away from the liquid trade waste generating area					
Report on other stormwater management options considered and why they are not feasible					
Identify the water supply source					
Bore / groundwater / on-site dam / watercourse Town water					
Recycled / reuse water Any water supply meter being installed					
Flow measurement location and proposed flow measurement to sewer (attach details of flow measurement installed / proposed)					
Application to be accompanied by two copies of plans showing:					
 Details and location of all processes, tanks, pits and apparatus associated with the generation of industrial waste Details of the proposed liquid waste treatment processes Details of pipes, floor drainage used to convey the effluent A full schematic layout of the proposed / existing waste pre-treatment facilities for liquid trade waste prior to discharge to the sewerage system 					
 Flow diagram and hydraulic profile of proposed treatment apparatus Capacity / dimensions, material of construction and lining, operation and maintenance of all pits, tanks, dosing systems, pumps, etc 					
• Details of the integrity of the pH correction system (diversion system, recording, alarms - location, fail-safe, tamper-proof)					

Proposed cleaning schedule of pre-treatment equipment and contractor					
Substance	Qty	Storage liquid / solid	Location	Bunding	
NOTE: Attach Material Safety Data Sheets prepared in accordance with the National Code of Practice (NOHSC:2011) for chemicals to be used and are likely to be contained in the waste effluent					
Any proposed plans for future expansion? (If Yes, give details on a separate attachment) YES NO					